




RAMSYS

LM 211S™

Off-line Gamma Liquid Monitor

Sampling liquid from a pipe, a tank or a pool. Can withstand seismic conditions. Version with a 4π 2" shielding.



FEATURES

- Energy spectrum and temperature changes compensation
- Available with or without display or local signaling
- Seismically qualified
- Available under 10 CFR 50 App.B, ASME NQA-1 and IEC61226 programs for safety related applications

DESCRIPTION

The LM 211S from the RAMSYS product line has been developed to sample liquid from a pipe, a tank or a pool. A 1¼"x1" NaI scintillation detector face a liquid sampler inside a 4 π lead shielding for the gamma emitting isotope monitoring.

A radioactive source ²⁴¹Am built into the NaI scintillator allows compensation of potential drift whenever temperature changes occur.

The spectrometry capability, based on a 1024-channel spectrum analysis, allows immediate and easy radio isotope identification in case of alarm.

LM 211S | OFF-LINE GAMMA LIQUID MONITOR

PHYSICAL CHARACTERISTICS

- Radiation detected: gamma
- Detector: 1¼" x1" NaI(Tl) scintillator + PMT with ²⁴¹Am source (SG/NAI 1¼"x1")
- Lead thickness: 4 π/5 cm (4 π/2 in)
- Energy range: 100 keV to 2.5 MeV
- Measurement range: 3.7 10⁺³ to 3.7 10⁺⁹ Bq/m³ (10⁻⁷ to 10⁻¹ μCi/cc)

ENVIRONMENTAL CHARACTERISTICS

- Normal temperature: +5°C to +40°C (+41°F to +104°F)
- Temperature limit: -5°C to +55°C (+23°F to +131°F)
- MTBF: > 20 000 hours, with preventive maintenance
- TID:
 - Processing unit: 100 Gy (10⁺⁴ rad)
 - Detector: 10⁺³ Gy (10⁺⁵ rad)

PNEUMATIC CHARACTERISTICS

- Standard flow rate: 10 l/min (0.57 scfm)
- Beaker volume: 4.3 l

MECHANICAL CHARACTERISTICS

- Dimensions (detection subassembly): 1002 mm (39.4 in) x Ø 478 mm (18.8 in)
- Weight (detection subassembly): ~ 300 kg (~ 661 lb)
- Color: gray RAL 7030 (decontaminable paint)

ELECTRICAL CHARACTERISTICS

- Power supply: refer to possible versions
- Data link outputs: 1 RS232 (LPDU only) and 2 isolated RS485
- Alarm relays: 3 SPDT relays
- I/O: 2 isolated analog outputs and 1 isolated analog input (0/4-20 mA)

SIGNALING (Applicable to LPDU only)

- Alphanumeric display: measurement, status...
- Sound alarm: buzzer 90 dBA at 1 meter
- Visual alarm: 3 lights (red, yellow, green)

REFERENCE STANDARDS

- Nuclear: IEC60861
- Environmental: IEC/IEEE 60780-323
- Seismic: IEC60980, IEEE344
- EMC: 2014/30/EU and 2014/35/EU, EPRI 102323, RG 1.180, IEC61000-6-2 and IEC61000-6-4

VERSIONS

- 230 Vac or 230 Vac + 400 Vac 3Ø or 120 Vac + 400 Vac 3Ø
- Local processing and display unit (LPDU) or local processing unit (LPU)
- Valve plate
- Pumping system

ACCESSORIES

- Calibration tools
- Software: MASS2, RAMVISION, SIMS2...
- USB converters
- Seismic qualified wall mounting bracket for LP(D)U

Featuring:



www.mirion.com

Copyright © 2019 Mirion Technologies, Inc. or its affiliates. All rights reserved. Mirion, the Mirion logo, and other trade names of Mirion products listed herein are registered trademarks or trademarks of Mirion Technologies, Inc. or its affiliates in the United States and other countries. Third party trademarks mentioned are the property of their respective owners.

144398EN-H



MIRION
TECHNOLOGIES