



AMP-200

GM Tube-Based Ratemeter and Area Monitor



Nuclear
Power



Homeland
Security
& Defense



Industrial and
Manufacturing



Healthcare



Labs and
Education

OVERVIEW

The AMP-200 provides real-time remote radiological monitoring. Local readout of hand-held meter allows for use as a portable survey instrument.

More importantly, since the probe's sensitive electronics are located far from the high field (25 to 350 feet away), they are not subject to destructive gamma exposure. The probe head may be placed directly into a filter compartment or against a resin tank or waste liner.

KEY FEATURES

The AMP-50 is designed specifically to be used in high dose rate fields. The AMP-200 features linear response from 5 R/hr to 10,000 R/hr (0.5 msv/hr to 100 sv/hr)

- Rugged construction, waterproof detector housing and cable
- Quick-disconnect connectors allow customization of cable length and facilitate easy decontamination
- Built-in communication port for use with DDC-16, WRM transmitter..
- «Smoothed» digital display offers accurate, stable readings
- User-selectable internal alarm threshold

Health Physics Division

RADIOLOGICAL CHARACTERISTICS

- Detector: energy compensated GM-tube
- Detection range ($\pm 10\%$): 0.5R/hr to 10,000 R/hr
- Energy range sensitivity: 11 cps per R/hr

ELECTRICAL CHARACTERISTICS

- Power supply: 9 Volts (supplied by a 9 Volt battery located in the meter case)
- Optional 9 Volt AC adapter available
- Battery life: approximately 50 hours of continuous use

MECHANICAL CHARACTERISTICS

- Meter dimensions (w x h x d): 6.8 x 11.9 x 1.2 cm (2.7 x 4.7 x 0.5 in)
- Probe head length: 16.5 cm (6.5 in)
- Diameter: 3.3 cm (1.3 in)
- Standard cable length: 7.6 m (25 ft)
- Maximum cable length: 106 m (350 ft)

ENVIRONMENTAL CHARACTERISTICS

- Temperature: -10° to 50°C (15 to 120°F)
- Relative humidity: 10 to 95% RH (non-condensing)

> CHINA - SHANGHAI

T: +86 21 6180 6920 | info-cn@mirion.com

> FINLAND - TURKU

T: +358 2 4684 600 | info-fi@mirion.com

> FRANCE - LAMANON

T: +33 (0) 4 90 59 59 59 | E: info-fr@mirion.com

> GERMANY - HAMBURG

T: +49 40 85193 0 | E: info-de@mirion.com

> USA - SMYRNA, GEORGIA

T: +1 770 432 2744 | E: info-us@mirion.com

Copyright (c) 2014 Mirion Technologies, Inc. or its affiliates. All rights reserved. Mirion, the Mirion logo, and other trade names of Mirion products listed herein are registered trademarks or trademarks of Mirion Technologies, Inc. or its affiliates in the United States and other countries. Third party trademarks mentioned are the property of their respective owners.