




# Ge Detector Accessories

## Model 7413, 7413F Detector Tripod




- For field measurements
- Heavy duty construction
- 7413 accommodates Slimline, MAC or Big MAC
- 7413F accommodates Flanged, MAC or Big MAC
- Detector element elevation (>30 cm to <120 cm)
- Built-in level
- Shipping weight – 9 kg (20 lb)

## Model 757 Tungsten Shield/Collimator




- High density (17 g/cc)
- Compact
- Requires special MAC
- Specify collimator opening
- Dimensions: 7.7 cm I.D. x 17.8 cm O.D. x 20.3 cm long (3.05 x 7.0 x 8.0 in.)
- Shipping weight - 85 kg (187 lb)

## Model 7415 Detector Lift



- Accommodates MAC, Big MAC and Cryoelectric II
- Compatible with CANBERRA shields
- Convenient and safe operation


## Model 717 Portable Detector Shield



- For MAC or Big MAC
- 89 mm I.D. x 165 mm long (3.5 x 6.5 in.)
- 25 mm (1.0 in.) thick lead
- Brass lined-steel jacketed
- Shipping weight – 34.5 kg (76 lb)

# Ge Detector Accessories

## Model 707 Lead Shield




- Economical and light weight
- For Slimline cryostats
- Construction: steel jacket, lead bulk, Sn/Cu liner
- Dimensions:
  - 152 mm (6 in.) inside diameter
  - 254 mm (10 in.) inside depth
  - 51 mm (2 in.) lead thickness
- Table included: 61 x 61 cm (24 x 24 in.) x 68-76 cm (27-30 in.) high
- Shipping weight – 250 kg (550 lb)

## Model 707M Modular Lead Shield




- Modular construction
- Maximum component weight – 227 kg (500 lb)
- For Slimline cryostats
- Construction: steel jacket, chevron lead rings, Sn/Cu liner
- Dimensions:
  - 152 mm (6 in.) inside diameter
  - 254 mm (10 in.) inside depth
  - 102 mm (4 in.) shield thickness
- Table included: 61 x 61 cm (24 x 24 in.) x 68-76 cm (27-30 in.) high
- Shipping weight – 646 kg (1425 lb)

## Model 7411 Detector Submarine



- Accommodates single-port MAC
- 6 m (20 ft) umbilical hose (longer available)
- Ballast for fresh or salt water (specify)
- Body Dimensions – 178 mm diameter x 591 mm long (7 x 23.25 in.)
- Shipping weight – 20 kg (45 lb)

## Model 7412 Annealing Kit



- Fix radiation damage *in situ*
- Includes:
  - Valve operator
  - Temperature controller (115 V ac only)
  - Heating tape or air heater (MAC)
- Specify cryostat type
- Shipping weight – 5 kg (11 lb)

Note: Controller subject to change with availability.