



RAMSYS

GIM 202K™

Wide Range Gamma Area Monitor

Continuous monitoring of gamma dose rate under mild or post-accident environmental conditions.



FEATURES

- Wide measurement range
- Compact and reliable
- Available with or without display and local signalling
- Available under 10 CFR 50 App.B, ASME NQA-1 and IEC61226 programs for safety related applications

DESCRIPTION

The GIM 202K forms part of the RAMSYS product line. It has been developed to monitor kerma dose rate (in Gy/h or rad/h) or ambient equivalent dose rate $H(^*10)$ (in Sv/h or rem/h) in nuclear facilities under mild operating or post-accident conditions.

The very simple concept of its ionization chamber allows this monitor to have a great reliability of prime importance in the safety related applications.

GIM 202K | WIDE RANGE GAMMA AREA MONITOR

PHYSICAL CHARACTERISTICS

- Radiation detected: gamma
- Detector: stainless steel ionization chamber (KG 220 SEF-Gy for Gy/h or KG 220 SEF-Sv for Sv/h)
- Energy range: 80 keV to 1.5 MeV according to IEC60532
- Energy range capability: up to 7 MeV ($\pm 60\%$)
- Typical measurement range: 10^{-7} to 10^{+2} Gy/h or Sv/h (10^{-5} to 10^{+4} rad/h or rem/h)

ENVIRONMENTAL CHARACTERISTICS

- Normal temperature:
 - Processing unit: $+5^{\circ}\text{C}$ to $+40^{\circ}\text{C}$ ($+41^{\circ}\text{F}$ to $+104^{\circ}\text{F}$)
 - Detector: -30°C to $+100^{\circ}\text{C}$ (-22°F to $+212^{\circ}\text{F}$)
- Temperature limit:
 - Processing unit: -5°C to $+55^{\circ}\text{C}$ ($+23^{\circ}\text{F}$ to $+131^{\circ}\text{F}$)
 - Detector: 120°C (248°F) during 1 hour
- MTBF: > 50 000 hours
- TID:
 - Processing unit: 100 Gy (10^{+4} rad)
 - Detector: $2.5 \cdot 10^{+5}$ Gy ($2.5 \cdot 10^{+7}$ rad)
- Protection index:
 - Processing unit: IP65 and IK07
 - Detector: IP65, IP67 and IK07

MECHANICAL CHARACTERISTICS

- Dimensions:
 - Processing unit: 390 mm x 196 mm x 187 mm (15.3 in x 7.7 in x 7.3 in)
 - Detector: 240 mm (9.5 in) x \varnothing 280 mm (11 in)
- Weight:
 - Processing unit: 8.5 kg (18.7 lb)
 - Detector: 23 kg (51 lb)
- Color: gray RAL 7030 (decontaminable paint)

ELECTRICAL CHARACTERISTICS

- Power supply: 230 Vac – 50 Hz or 120 Vac – 60 Hz
- Data link outputs: 1 RS232 (LPDU only) and 2 isolated RS485
- Alarm relays: 3 SPDT relays
- I/O: 2 isolated analog outputs and 1 isolated analog input (0/4-20 mA)

SIGNALING (Applicable to LPDU only)

- Alphanumeric display: measurement, status...
- Sound alarm: buzzer 90 dBA at 1 meter
- Visual alarm: 3 lights (red, yellow, green)

REFERENCE STANDARDS

- Nuclear: IEC60532
- Environmental: IEC/IEEE 60780-323
- Seimisc: IEEE344 and IEC60980
- EMC: 2014/30/EU and 2014/35/EU, EPRI 102323, RG1.180, IEC61000-6-2 and IEC61000-6-4

VERSIONS

- 230 Vac or 120 Vac
- Local processing and display unit (LPDU) or local processing unit (LPU)
- KG 220 SEF-Gy or KG 220 SEF-Sv
- With or without RS485 junction box
- Detector cable length: from 10 m (32.8 ft) to 70 m (229.6 ft)
- Junction box cable length: 2 m (6.56 ft), 5 m (16.4 ft) or 10 m (32.8 ft)

ACCESSORIES

- Calibration tools
- Software: MASS2, RAMVISION, SIMS2...
- USB converters
- Seismic qualified wall mounting bracket for LP(D)U
- Ethernet (LPDU only)

Featuring:



www.mirion.com

Copyright © 2019 Mirion Technologies, Inc. or its affiliates. All rights reserved. Mirion, the Mirion logo, and other trade names of Mirion products listed herein are registered trademarks or trademarks of Mirion Technologies, Inc. or its affiliates in the United States and other countries. Third party trademarks mentioned are the property of their respective owners.

144176EN-J



MIRION
TECHNOLOGIES